

Proof of delivery
REGUPOL Germany GmbH & Co. KG
 Am Hilgenacker 24
 57319 Bad Berleburg
 +49 2751 803-0
commercial@regupol.de
www.commercial.regupol.com

Position	Quantity	Scope of work	Unit price	Total price
1	m ²	Subfloor preparation The substrate prepared for installation must comply with the requirements of the applicable national standards. Attention must be paid to VOB Part C – DIN 18365 as well as the increased requirements for finished floor surfaces according to DIN 18202, Table 3, Line 4 . Furthermore, all EN and DIN standards recognized at the time of execution, as well as the generally accepted rules of trade and state of the art, shall apply.	€/m ²	€
2	m ²	REGUPOL upscale® 4 mm heterogeneous resilient commercial floor covering. Supply and installation. Design: _____ LRP® Dimensions: 1.200 x 230 x 4 mm Including beveled edge Material: EPDM granules and PUR binder, factory sealed. Performance fleece backing to facilitate easier deinstallation. Thickness (EN ISO 24346): 4 mm. Weight (EN ISO 23997) approx. 4.0 kg/m ² . Reaction to Fire (EN 13501-1): Cfl-s1. Slip Resistance (EN 16165, Annex B): R10. Impact Sound Reduction (EN ISO 10140): 14 dB. VOC emissions: Assessment according to AgBB 2021 — requirements fulfilled.	€/m ²	€

CE marking according to EN 14041 —
information to follow.

The floor covering must be installed in
accordance with the installation guidelines of
both the adhesive manufacturer and the
flooring manufacturer.

3	lm	Baseboards:	€/lm	€
		The use of adhesive insert baseboards is recommended. This solution creates a seamless visual transition from the floor covering onto the wall. Cut stripes from the specified flooring to match the required width of the self-adhesive baseboard and insert them accordingly. Install the baseboard on the wall properly and in accordance with standard industry practices.		

Total: €