MAHN Lamellen		Louvre window S9				
status:		enquiry	order			
project number:			purchase order:			
project manager:			phone number:		o)	
desired delivery date:			date:		outside	inside inside
project:			•		no	.⊑
delivery address:						
contact person on site:						
Item:		01	02	03		
	no.:					
v	width: (mm)					
frame dimensions	height:					
	type of frame:		type 1	type 1		
		type 2 type 3	type 2 type 3	type 2 type 3		
fra		thickness:mm (see detail glazingprofile)	thickness:mm (see detail glazingprofile)	thickness:mm (see detail glazingprofile)		eight
	no. of blades:	, , ,	, ,	, ,		d suc
9	glass		8mm	8mm		dimensions height
el type	thickness:	☐ 10mm ☐ 12mm	10mm	☐ 10mm ☐ 12mm		le dir
blade pane	type of glass:	tougheried glass	toughened glass	toughened glass		frame
olade		☐ laminated glass☐ float glass	☐ laminated glass☐ float glass	☐ laminated glass☐ float glass		
	finish:	powder coated natural anodised	powder coated natural anodised	powder coated natural anodised		
finish	colour supplier & RAL colour:			_		
controls	type of control:	manual electric V	manual electricV	manual electricV		
		pneumatic	pneumatic	pneumatic		
	description:					
	cable length: (standard = 2,5m)	m	m	m		
	cable exit: (LAH 65 only)	bottom	top bottom	top bottom		
	control	side through frame position A (right side)	side through frame position A (right side)	side through frame position A (right side)		
	position:	position B (left side)	position B (left side)	position B (left side)	Frame	
	fixing brackets /	height mm	height mm	height mm	type 1	
special adaptor: smoke vents yes		yes	yes	yes		46.8
	CE- certified:		no no	no no		
Frame type 1 51.5 frame dim			B 8'94 51.5		Frame type 2	20 2 6 10
Frame type 3 Frame type 2 September 2024 / Subject to change without notice					Frame type 3	20,25 40