



 HAHN Lamellen		Louvre window S9-iV		
status:		☐ enquiry	☐ order	
project number:			purchase order:	
project manager:			phone number:	
desired delivery date:			date:	
project:				
delivery address:				
contact person on site:				
Pos.:		01	02	03
no.:				
frame dimensions	width: (mm)			
	height: (mm)			
	type of frame: ☐ type 1 ☐ type 2 ☐ type 3 thickness: _____ mm (see detail glazingprofile)	☐ type 1 ☐ type 2 ☐ type 3 thickness: _____ mm (see detail glazingprofile)	☐ type 1 ☐ type 2 ☐ type 3 thickness: _____ mm (see detail glazingprofile)	
no. of blades:				
blade panel type	thickness: (mm)	24mm	24mm	24mm
	type of filling:	☐ double glazed ☐ insulated blades	☐ double glazed ☐ insulated blades	☐ double glazed ☐ insulated blades
	glass design: standard: outer side: 6mm air space: 12mm inner side: 6mm	outer side: _____ mm air space: _____ mm inner side: _____ mm	outer side: _____ mm air space: _____ mm inner side: _____ mm	outer side: _____ mm air space: _____ mm inner side: _____ mm
	type of glass:			
finish	finish:	☐ powder coated ☐ natural anodised	☐ powder coated ☐ natural anodised	☐ powder coated ☐ natural anodised
	colour supplier & colourcode:			
controls	type of control:	☐ manual ☐ electric _____ V ☐ pneumatic	☐ manual ☐ electric _____ V ☐ pneumatic	☐ manual ☐ electric _____ V ☐ pneumatic
	description:			
	cable length: (standard = 2,5m)	_____ m	_____ m	_____ m
	cable exit: (LAH 65 only)	☐ top ☐ bottom ☐ side through frame	☐ top ☐ bottom ☐ side through frame	☐ top ☐ bottom ☐ side through frame
	control position:	☐ position A (right side) ☐ position B (left side) height _____ mm	☐ position A (right side) ☐ position B (left side) height _____ mm	☐ position A (right side) ☐ position B (left side) height _____ mm
fixing brackets / special adaptor:				
smoke vents CE- certified:		☐ yes ☐ no	☐ yes ☐ no	☐ yes ☐ no




Frame type 1


Frame type 2




Frame type 3



Frame type 1



Frame type 2



Frame type 3

